



### Highlights

- >> Eight High-Speed WAN Ports
  
- >> Two 10/100 Base-T Ethernet Ports
  
- >> Based on Dual Motorola MPC8255 PowerQUICC II™ Processors
  
- >> 128 MB of Shared DRAM Memory
  
- >> SNMP Support
  
- >> Open, Fully Documented API
  
- >> Supports Complete Line of NexusWare® WAN Protocol Software
  
- >> Capable of Server-Resident Multi-Protocol Processing

The MPS1000 is a WAN/LAN data communications server that is attached to a local area network to provide wide-area connectivity. A single MPS1000 communications server can support a number of WAN protocols, each of which can be accessed simultaneously by multiple clients.

The MPS1000 provides two 10/100 Ethernet ports and eight high-speed WAN serial ports, making it ideal as an intelligent WAN/LAN bridge, a WAN/LAN gateway device, or a remote WAN connectivity server. By using the MPS1000 as an SNMP management device, any computer and/or workstation equipped with TCP/IP on the LAN can access information from the communications server.

The MPS1000 is designed to preserve the user's software investment by enabling applications to be moved to any of Performance Technologies' WAN products. Its modular design supports virtually any serial communications protocol.

### NexusWare® Software Support

With a well-defined application programming interface (API), Performance Technologies' integrated protocol suite reduces time-to-market by eliminating unnecessary development time at the hardware/protocol level. The protocols for the standard WAN hardware products enable development engineers to proceed directly to integration and application development efforts.

Performance Technologies' comprehensive suite of NexusWare® WAN communications protocols provides complete WAN connectivity solutions for Radar Receiver/SBSI, Frame Relay, HDLC, LAPD, and X.25 protocols. Operating system support includes Solaris™, Windows®, and Linux®.

### Hardware Features

The MPS1000 is designed as a fully programmable communications system capable of sustaining high data rates for the variety of protocols used in synchronous communications.

The MPS1000 utilizes dual Motorola MPC8255 PowerQUICC II™ communications microprocessors. One of the processors is configured as the master, while the other is configured as the slave. The default mode of operation uses the slave processor with its CPU core disabled, leaving the CPM active for serial communication.

Two external Ethernet PHYs are offered to provide Ethernet redundancy. The MPS1000 will automatically switch over to the secondary Ethernet PHY if a link is lost on the primary PHY.

The MPS1000 supports eight identical, individually programmable, synchronous serial I/O ports. The ports are capable of electrically interfacing to V.35, RS-530, RS-449, and RS-232 equipment. Each port is brought out in groups of four to an 80-pin connector that supports Performance Technologies' quad-connection Hydra line of serial I/O cables.



# MPS1000

## Eight-Channel Multi-Protocol Communications Server

### Ordering Information

- >> **PT-MPS1000-12159**  
MPS1000 Multi-Protocol WAN/LAN Communications Server

#### Cable Options

- >> **PT-ACC334-11918**  
4 x V.35 Hydra Cable, DTE with Thumbscrews
- >> **PT-ACC334-11919**  
4 x RS232 Hydra Cable, DTE with Jackscrews
- >> **PT-ACC334-12274**  
4 x RS232 Hydra Cable, DTE with Thumbscrews
- >> **PT-ACC334-11969**  
4 x EIA530 Hydra Cable, DTE with Jackscrews
- >> **PT-ACC334-12273**  
4 x EIA530 Hydra Cable, DTE with Thumbscrews
- >> **PT-ACC334-11920**  
4 x RS449 Hydra Cable (Socket) Sun Substitute, DTE with Jackscrews
- >> **PT-ACC334-11921**  
4 x RS449 Hydra Cable (Pin), DTE with Jackscrews
- >> **PT-ACC358-11971**  
4 x V.35 Hydra Cable, DCE with Thumbscrews
- >> **PT-ACC358-12275**  
RS232 Debug Cable (console)

#### Software Options

- >> This product is available with a variety of software options. For more information contact sales@pt.com.



**Corporate Headquarters:**  
Performance Technologies  
205 Indigo Creek Drive  
Rochester, NY 14626

Tel: 585.256.0200  
Fax: 585.256.0791  
E-mail: sales@pt.com

[www.pt.com](http://www.pt.com)

With either rack-mountable or freestanding configurations, the MPS1000 provides the power to handle full-load network traffic and communicates via TCP/IP with clients on the LAN.

### Multi-Protocol Networking Capabilities

With the multi-protocol architecture of the MPS, both standard and custom protocols supplied by Performance Technologies can coexist on the same server with client-developed protocols. A single MPS server provides the unique combination of WAN and LAN protocols needed to provide an integrated networking solution.

### Technical Specifications

#### Configuration

- Eight WAN ports – up to 2 Mbps bi-directional, simultaneously
- Two LAN ports at 10/100 Mbps

#### Processor

- 233 MHz Motorola MPC8255 PowerQUICC® II processors

#### Memory

- Two x 128 MB shared DRAM
- Two x 32 MB application flash PROM
- Two x 512 KB boot PROM

#### Physical Interface

- WAN ports
  - DB25: RS-232/530
  - DB37: RS-449
  - M34: V.35
- LAN port
  - RJ45

#### Electrical Interfaces

- WAN: V.35, RS-530, RS-449, and RS-232 (via external adapter)
- LAN: 10/100 Base-T Ethernet

#### SNMP Support

- SNMP (Basic MIB II) support which allows MIB browser or SNMP management of the server

#### Certifications

- FCC Class A
- CE
- UL

#### MTBF

- 81,473 hours per Bellcore SR-332 Issue 1

#### Power Requirements

- 2 A at 115 V
- 0.9 A at 230 V

#### Physical Dimensions

- 432 mm (W) x 280 mm (D) x 44.5 mm (H) (17.0 in. x 11.02 in. x 1.75 in.)

#### Weight

- Packaged: 8.35 kg (18.4 lb)
- Unpackaged: 5.44 kg (12 lb)

#### Enclosure

- 19-in. rackmount or tabletop

#### Temperature

- Operating: 0 to 50°C (32 to 122°F)
- Storage: -40 to 70°C (-40 to 158°F)